

## [2017-July-NEWSFree 352-001 PDF Dumps Offered by Braindump2go[101-110

2017/July New Cisco 352-001 Exam Dumps with PDF and VCE Updated in [www.Braindump2go.com](http://www.Braindump2go.com) Today for Free Download!  
100% Real Exam Questions! 100% Exam Pass Guaranteed! 1.|2017 New 352-001 Exam Dumps (PDF & VCE) 499Q&As  
Download:<http://www.braindump2go.com/352-001.html> 2.|2017 New 352-001 Exam Questions & Answers Download:  
<https://drive.google.com/drive/folders/0B75b5xYLjSSNSUNBNi1aYkpfOTQ?usp=sharing> QUESTION 101Which two features  
can be used to extend VRFs across a campus? (Choose two.) A. 802.1q trunksB. LDPC. MPLS TED. GREE. port channels  
Answer: AD QUESTION 102You are asked to design a large campus network that will be using multicast for data transport. Which  
feature should be enabled at the Layer 2 access edge for host-only ports? A. PortFastB. BPDU guardC. PIM-SMD. PIM  
query interval Answer: A QUESTION 103After the recent implementation of a new design that incorporated GRE tunnels into the  
network, the network operations staff is seeing the following syslog message in multiple routers on the network -  
%TUN-5-RECURDOWN: Tunnel0 temporarily disabled due to recursive routing.From a design perspective, what was not taken  
into account prior to implementing the solution? A. The neighboring routers cannot respond within the specified hold time.B.  
The interface on the router that is the source of the tunnel is down.C. The interface on the neighboring router that is the source of  
the tunnel is down.D. The router is learning the route to the tunnel destination address using the tunnel interface.E. The tunnel  
interface on the router is not receiving any keepalives within the specified hold time. Answer: D QUESTION 104A company plans  
to establish a new network using Cisco Catalyst switches for its multicast applications. What is the disadvantage when two multicast  
applications are using the multicast IP addresses 234.17.4.5 and 234.145.4.5 inside the same network? A. Multicast packets from  
both applications are flooded to all Layer 2 ports in a segment where a multicast receiver is located.B. Multicast packets from both  
applications are flooded to ports where one multicast receiver from one application is located.C. Only one multicast stream is  
received at the port where the receivers from both applications are located.D. Both multicast senders will always receive the  
multicast packets from the other multicast application.E. The routers doing PIM-SM cannot distinguish between the two multicast  
applications. Answer: B QUESTION 105Which design concern should be accounted for in all Layer 3 virtualization technologies?  
A. Layer 3 redundancyB. packet sizingC. application usageD. Layer 3 stability Answer: B QUESTION 106A many-to-many  
enterprise messaging application is using multicast as a transport mechanism. As part of the network design for this application,  
which multicast address should be used, according to best practices outlined in RFC 2365? A. 224.0.0.60B. 232.192.0.60C.  
239.128.0.60D. 239.193.0.60 Answer: D QUESTION 107Refer to the exhibit. You are planning the design of an encrypted WAN.  
IP packets will be transferred over encrypted GRE tunnels between routers B and C. The packet size is limited to a maximum of  
1500 bytes inside the WAN between routers B and C. If endpoint 1 tries to send 1500-byte IP packets to endpoint 2, in what three  
ways will the network design handle the fragmentation in three different possible network configurations? (Choose three.) A.  
When router B fragments packets after the encryption, router C must reassemble these fragmented packets.B. When router B  
fragments packets before the encryption, router C must reassemble these fragmented packets.C. When router B fragments packets  
after the encryption, the endpoint 2 must reassemble these fragmented packets.D. When router B fragments packets before the  
encryption, endpoint 2 must reassemble these fragmented packets.E. When router A fragments packets, router C must reassemble  
these fragmented packets.F. When router A fragments packets, endpoint 2 must reassemble these fragmented packets. Answer:  
ADF QUESTION 108When a design calls for spanning VLANs across a campus network, what are two issues that need to be  
addressed in the design? (Choose two.) A. network convergenceB. network accessibilityC. fault isolationD. application  
scalabilityE. user experience Answer: AC QUESTION 109Which two aspects are considered when designing a dual hub, dual  
DMVPN cloud topology? (Choose two.) A. recommended for high availabilityB. requires all sites to have dual Internet  
connectionsC. spoke-to-spoke traffic will transit the hub unless spokes exchange dynamic routing directlyD. hub sites must  
connect to both DMVPN cloudsE. will only work with single-tier headend architecture Answer: AE QUESTION 110When  
creating a network design, which one of these options provides for basic Layer 2 client isolation to prevent broadcast traffic  
exposure? A. SVIB. VLANC. routed portD. edge port Answer: B QUESTION 111When adding an IPSec headend  
termination device to your network design, which two performance indicators are the most accurate to determine device scalability?  
(Choose two.) A. CPU capabilitiesB. bandwidth capabilitiesC. packets per second capabilitiesD. maximum tunnel  
termination capabilities Answer: CD !!!RECOMMEND!!! 1.|2017 New 352-001 Exam Dumps (PDF & VCE) 499Q&As  
Download:<http://www.braindump2go.com/352-001.html> 2.|2017 New 352-001 Study Guide Video: YouTube Video:  
[YouTube.com/watch?v=mTLcNm1jZow](https://www.youtube.com/watch?v=mTLcNm1jZow)